

advanced devices

Catalog # CL40FR

CL Series Female Receptacle

Panel Mount 400A/600V, Double Set Screw
NEMA 3R, 4 when mated with shrouded device.

- Use 2/0 to 4/0 cable, copper.
- Strip cable jacket 1-3/4 inch.
- Wrap foil around strands, insert into contact and tighten setscrews (2) to 150 in.-lbs. of torque. Do not over tighten.

CAUTION: The female cam alignment button on cam –type devices will withstand up to approximately 40 ft.-lbs. of torque. Care should be exercised when attaching a "Hard 3-fer" to a panel mount. Excessive torque applied to the 3-fer may result in a collapse of the cam button.



advanced devices

Catalog # CL40FR

CL Series Female Receptacle

Panel Mount 400A/600V, Double Set Screw
NEMA 3R, 4 when mated with shrouded device.

- Use 2/0 to 4/0 cable, copper.
- Strip cable jacket 1-3/4 inch.
- Wrap foil around strands, insert into contact and tighten setscrews (2) to 150 in.-lbs. of torque. Do not over tighten.

CAUTION: The female cam alignment button on cam –type devices will withstand up to approximately 40 ft.-lbs. of torque. Care should be exercised when attaching a "Hard 3-fer" to a panel mount. Excessive torque applied to the 3-fer may result in a collapse of the cam button.



advanced devices

Catalog # CL40FR

CL Series Female Receptacle

Panel Mount 400A/600V, Double Set Screw
NEMA 3R, 4 when mated with shrouded device.

- Use 2/0 to 4/0 cable, copper.
- Strip cable jacket 1-3/4 inch.
- Wrap foil around strands, insert into contact and tighten setscrews (2) to 150 in.-lbs. of torque. Do not over tighten.

CAUTION: The female cam alignment button on cam –type devices will withstand up to approximately 40 ft.-lbs. of torque. Care should be exercised when attaching a "Hard 3-fer" to a panel mount. Excessive torque applied to the 3-fer may result in a collapse of the cam button.



advanced devices

Catalog # CL40FR

CL Series Female Receptacle

Panel Mount 400A/600V, Double Set Screw
NEMA 3R, 4 when mated with shrouded device.

- Use 2/0 to 4/0 cable, copper.
- Strip cable jacket 1-3/4 inch.
- Wrap foil around strands, insert into contact and tighten setscrews (2) to 150 in.-lbs. of torque. Do not over tighten.

CAUTION: The female cam alignment button on cam –type devices will withstand up to approximately 40 ft.-lbs. of torque. Care should be exercised when attaching a "Hard 3-fer" to a panel mount. Excessive torque applied to the 3-fer may result in a collapse of the cam button.

