



Catalog #CLS40FRSB
CLS Series Female Receptacle

**Panel Mount 400A/600V, 1/2-13 Threaded Stud
NEMA 3R, 4 when mated with shrouded device.**

- Use up to 250-MCM cable, copper.
- Attach appropriate ring terminal to end of cable.
- Locate ring terminal over stud and secure with lock washer and nut to 25 ft.-lbs. of torque. Do not over-tighten.

CAUTION: The female cam alignment button on cam – type devices will withstand up to approximately 40 ft.-lbs. of torque. Care should be exercised when attaching a “3-fer” to a panel mount. Excessive torque applied to the 3-fer may result in a collapse of the cam button.



Tech Support and Customer Service 800.307.6702
Email: Technical@Marinco.com
Website: www.marincopowerproducts.com

08/16 470188



Catalog #CLS40FRSB
CLS Series Female Receptacle

**Panel Mount 400A/600V, 1/2-13 Threaded Stud
NEMA 3R, 4 when mated with shrouded device.**

- Use up to 250-MCM cable, copper.
- Attach appropriate ring terminal to end of cable.
- Locate ring terminal over stud and secure with lock washer and nut to 25 ft.-lbs. of torque. Do not over-tighten.

CAUTION: The female cam alignment button on cam – type devices will withstand up to approximately 40 ft.-lbs. of torque. Care should be exercised when attaching a “3-fer” to a panel mount. Excessive torque applied to the 3-fer may result in a collapse of the cam button.



Tech Support and Customer Service 800.307.6702
Email: Technical@Marinco.com
Website: www.marincopowerproducts.com

08/16 470188



Catalog #CLS40FRSB
CLS Series Female Receptacle

**Panel Mount 400A/600V, 1/2-13 Threaded Stud
NEMA 3R, 4 when mated with shrouded device.**

- Use up to 250-MCM cable, copper.
- Attach appropriate ring terminal to end of cable.
- Locate ring terminal over stud and secure with lock washer and nut to 25 ft.-lbs. of torque. Do not over-tighten.

CAUTION: The female cam alignment button on cam – type devices will withstand up to approximately 40 ft.-lbs. of torque. Care should be exercised when attaching a “3-fer” to a panel mount. Excessive torque applied to the 3-fer may result in a collapse of the cam button.



Tech Support and Customer Service 800.307.6702
Email: Technical@Marinco.com
Website: www.marincopowerproducts.com

08/16 470188



Catalog #CLS40FRSB
CLS Series Female Receptacle

**Panel Mount 400A/600V, 1/2-13 Threaded Stud
NEMA 3R, 4 when mated with shrouded device.**

- Use up to 250-MCM cable, copper.
- Attach appropriate ring terminal to end of cable.
- Locate ring terminal over stud and secure with lock washer and nut to 25 ft.-lbs. of torque. Do not over-tighten.

CAUTION: The female cam alignment button on cam – type devices will withstand up to approximately 40 ft.-lbs. of torque. Care should be exercised when attaching a “3-fer” to a panel mount. Excessive torque applied to the 3-fer may result in a collapse of the cam button.



Tech Support and Customer Service 800.307.6702
Email: Technical@Marinco.com
Website: www.marincopowerproducts.com

08/16 470188